

HUB5T-L120-4M-UK

Rechargeable powerHub 5 mobile power tower with four UK AC mains outlets and a 1200 Wh battery



Battery capacity
Approximately 1200 Wh

Power outlets
Four UK 220-240 V AC mains sockets

Mobility
Five-star base with lockable castors

Management
onView web and mobile service with 3-year subscription

Product overview

The Zioxi HUB5T-L120-4M-UK is a full-height rechargeable mobile AC power bank for classrooms, offices, libraries and flexible working environments. It supplies mains power without requiring a floor box or permanent connection during use. Four UK outlets are integrated into the tower, while the replaceable lithium iron phosphate battery and control electronics are enclosed within the powder-coated aluminium housing.

- + Mobile mains power: Four UK AC outlets allow laptops and other moderate-power devices to operate away from fixed sockets.
- + Long-life battery: Replaceable LiFePO4 battery technology is rated for approximately 2400 full recharge cycles.
- + Fast recharge: Approximately 2.5 hours from fully discharged for the 1200 Wh configuration.
- + Integrated protection: Soft start, low/over-voltage, short-circuit, overload and over-temperature protection.
- + Smart management: onView supports remote control, charging schedules, battery-health monitoring, alerts and usage reports.

Dimensions: 1000 H x 350 mm diameter

Technical specifications

Product code	HUB5T-L120-4M-UK
Manufacturer	Zioxi
Product family	Rechargeable powerHub 5 tower
Product type	Mobile rechargeable AC power bank
Battery capacity	Approximately 1200 Wh
Battery technology	Deep-cycle, rechargeable and replaceable lithium iron phosphate (LiFePO4)
Battery cycle life	Approximately 2400 full recharge cycles
Recharge time	Approximately 2.5 hours from fully discharged
Power outputs	Four UK AC mains sockets
AC output voltage	220-240 V AC
UK socket protection	Each UK socket fitted with a 3.15 A fuse
Electrical protection	Soft start, low/over-voltage, short-circuit, overload and over-temperature protection
Power input	One UK mains socket required when recharging
External dimensions	1000 H x 350 mm diameter
Mobility	Five-star base with lockable castors
Construction	White powder-coated aluminium housing
Top finish	Compact laminate; white or lime green standard, other colours by request
Local controls	Display with touch buttons for wake, on/off, time extension and status information
Cloud management	Zioxi onView web console and mobile app
Included subscription	3-year onView subscription
Connectivity	2.4 GHz Wi-Fi connection required for onView cloud functions
Warranty	2 years for powerHub and electronics; battery covered under the battery manufacturer warranty

Usage limitation: The AC outlets are intended for moderate-power equipment. Do not use the powerHub with high-load appliances such as kettles, heaters or vacuum cleaners.

onView functions

- Remote power control and scheduled availability.
- Green-charge scheduling and automatic charge termination.
- Battery-health, temperature and recharge alerts.
- Usage, location and historical reporting.

Specification sources: current Zioxi rechargeable powerHub product and onView information, checked 3 August 2026. Product specifications may be updated without notice.