



DIRECT VIEW LED IN **LARGE FORMAT**

Experience the power of DV One+, an advanced LED display solution that combines durability with stunning visuals. Built with glue-on-board (GOB) technology, it ensures reliability and low maintenance. With a wide color gamut and a 6000:1 contrast ratio, it delivers lifelike images. Perfect for indoor advertising or conference rooms, DV One+ offers smooth visuals and high refresh rates. Available in large size options, DV One+ makes a statement in any space.



GO BEYOND WITH CLICK2CAST!

Compatible with the Newline Click2Cast dongle, a hassle-free hardware solution for one click casting. Just a single button to initiate wireless screen casting effortlessly.



NEWLINE INTERACTIVE ECOSYSTEM

The Newline Interactive Ecosystem streamlines operations with seamless tools for content sharing, signage management, and display control, optimizing workflows

CAST+ **DISPLAY MANAGEMENT PLUS**

SIGNAGE PRO

- Edge-to-Edge Ultra Slim Design
- Ultra High Refresh Rate
- Full HD Resolution
- Plug & Play
- Easy of Maintenance
- Lightweight Construction

135" **163"** **189"**

MODEL

DVOne+ 135"	DV-13524Plus
DVOne+ 163"	DV-16324Plus
DVOne+ 189"	DV-18924Plus

PANEL

Display Type	Direct LED
Lights Welding Type	GOB
Display Area	135": 3000 x 1687,5 mm 163": 3600 x 2025,5 mm 189": 4200 x 2363 mm
Display Ratio	16:9
Resolution	1920 x 1080 (FHD)
Brightness	550 cd/m ²
Contrast Ratio	6000:1
Pixel pitch	135": 1,56 mm 163": 1,875 mm 189": 2,18 mm
Viewing Angle	160°
Refresh Rate	3840 Hz
Display Life Time	100 000 hours
Operating Temperature	-10°C - 40°C
Operating Humidity	10% - 80% RH No Condensation

POWER CONSUMPTION

Standard Mode*	135": 580 W 163": 690 W 189": tbc W
Standby mode*	<0,5 W

SMART SYSTEM

CPU	A311D2
RAM	4 GB
Storage	32 GB
Operating System	AOSP
Wi-Fi	6

EXTRA FIRMWARE FEATURES

Wake-on-LAN	✓
Wake-on-WiFi	✓

SPEAKER

Speaker Position	Bottom front
Speaker Max.Power Output	135": 5 W x 1 163": 5 W x 1 189": 5W x 1

REAR I/O

HDMI IN 2.0 (4K @60 Hz)	1
HDMI OUT 2.0 (4K @60 Hz)	1
USB Type-A 3.0	1
LAN In (RJ45)	1
SPDIF Out	1
Audio Output (Jack 3,5 mm)	1
RS232	1

SIDE I/O

HDMI IN 2.0 (4K @60 Hz)	1
USB Type-B 2.0	1
USB Type-A 3.0	1
USB Type-C	1

DIMENSIONS / WEIGHT

Outline Dimensions (Excl. wall mount)	135": 3009 x 1704 x 66 mm 163": 3609 x 2042 x 66 mm 189": 4209 x 2379,5 x 66 mm
Net Weight	135": 152 Kg 163": 209,5 Kg 189": tbc Kg

NEWLINE SOLUTIONS COMPATIBILITY

Newline Software Ecosystem	Cast+, Signage Pro & Display Mangement Plus
Newline Accessories	Click2Cast

* The provided measures are indicative and subject to further adjustments. They are not yet considered definitive.