

Key Features

- 180Hz refresh rate Delivers ultra-smooth performance, reducing motion blur.
- 1ms MPRT response time provides Lightning-fast response for minimal input lag and a competitive edge.
- Variable Refresh Rate (VRR) eliminates screen tearing and reduce stuttering.
- Wide viewing angles with vibrant, consistent colors with SuperClear®
 IPS technology.
- Designed for comfort with adjustable features to support longer gaming sessions.



Product **Description**

The ViewSonic XG27G1 is a 27" FHD monitor featuring HDMI and DisplayPort. It is also equipped with SuperClear® IPS technology, delivering stunning image quality with brilliant visual performance. While the XG27G1's high 180Hz refresh rate supports smooth visuals and minimal input lag. You may think it doesn't get better than this, but it does. Not only will you get the job done — be it grueling gaming sessions, video and photo editing, or office assignments — you'll be working on a sleek, beautifully designed monitor.



Visit Us

www.viewsonic.com

Display Size (in.): 27	DISPLAY		CONTROLS	
Panol Type: PS Tachnology	Display Size (in.):	27	Physical Controls:	Up, Right, Down, Left, Power
Panel Type:	Viewable Area (in.):	27	On Screen Display:	ViewMode, Color Adjust, Manual
Resolution Type: FHD (Full HD) Temperature: 32°F to 104°F (0°C to 40°C) Static Contract Ratio: 1,000-f (pp) Humidity (non-condensing): 20% to 90% Dynamic Contract Ratio: HDR10 VESA Compatible: 100 × 100 mm High Dynamic Range: HDR10 VESA Compatible: 100 × 100 mm High Dynamic Range: HDR10 VESA Compatible: 100 × 100 mm High Dynamic Range: HDR10 VESA Compatible: 100 × 100 mm High Dynamic Range: HDR10 VESA Compatible: HDMI (v2.0): 32 - 210KHz Daplaybor (v1.4): 32 × 210KHz Daplaybor (v1.4):	Panel Type:	IPS Technology		
Static Contrast Ratio	Resolution:	1920 x 1080	OPERATING CONDITIONS	
Dynamic Contrast Ratio: S0M:1 WALL MOUNT VESA Compatible: 100 x 100 mm Institute Institu	Resolution Type:	FHD (Full HD)	Temperature:	32°F to 104°F (0°C to 40°C)
High Dynamic Range: HDR10 VESA Compatible: 100 x 100 mm	Static Contrast Ratio:	1,000:1 (typ)	Humidity (non-condensing):	20% to 90%
Impure LED LED Impure LED Impure LED Impure LED Impure LED LED Impure LED	Dynamic Contrast Ratio:	50M:1	WALL MOUNT	
Brightness 300 cd/m² (typ) Frequency Horizontals HDMI (v2.0): 32 - 210KHz	High Dynamic Range:	HDR10	VESA Compatible:	100 x 100 mm
Colors 16.7M	Light Source:	LED	INPUT SIGNAL	
Colors 16.7M Frequency Vertical: HDMI (v2.0): 48 ~ 165H2, DisplayFort (v1.4): 48 ~ 160H2 Color Space Support: 8 bit true VIDEO INPUT Aspeet Ratio: 16:9 VIDEO INPUT Response Time (MPRT): 1ms Digital Sync: TMDS - HDMI (v2.0): PCI-E - DisplayPort (v1.4): 48 ~ 180H2 Viewing Angles: 178° horizontal, 178° vertical ERGONOMICS Backlight Life (Hours): 30000 Hrs (Min) Height Adjust (mm): 150 Curvature: Flat Swive: 30° Refersh Rate (Hz): 180 Till (Forward/Back): -5° / 2° Variable Refresh Rate Technology: Ves (G-Sync compatible) Pivot (Right/Left): 90° / 90° Low Blue Light: Software solution WEIGHT (IMPERIAL) Net (Ms): -5° / 9° Color Gamut: NTSC: 80% size (Typ) sRGB: 113% size (Typ) Net (Hs): 10.6 8 Surface Treatment: Anti-Glare, Hard Coating (3H) WEIGHT (METRIC) WEIGHT (METRIC) Net (Without Stand (kg): 3.1 9 COMPATIBILITY 1920x1080 DIMENSIONS (IMPERIAL) (WXHXD) Packaging (in.	Brightness:	300 cd/m² (typ)	Frequency Horizontal:	
Aspect Ratio	Colors:	16.7M	5 V C I	
Aspect Nation Third Thir	Color Space Support:	8 bit true	Frequency Vertical:	DisplayPort (v1.4): 48 ~ 180Hz
New Note	Aspect Ratio:	16:9	VIDEO INPUT	
Backlight Life (Hours): 30000 Hrs (Min) Height Adjust (mm): 150	Response Time (MPRT):	1ms	Digital Sync:	
Curvature Flat Swive 30°	Viewing Angles:	178° horizontal, 178° vertical	ERGONOMICS	
Refresh Rate (Hz):	Backlight Life (Hours):	30000 Hrs (Min)	Height Adjust (mm):	150
Variable Refresh Rate Technology: Yes (G-Sync compatible) Pivot (Right/Left): 90° / 90° Low Blue Light: Software solution WEIGHT (IMPERIAL) Net (Ibs): 10.6 Flicker-Free: Yes NTSC: 80% size (Typ) sRGB: 113% size (Typ) Net Without Stand (Ibs): 6.8 Color Gamut: NTSC: 80% size (Typ) sRGB: 113% size (Typ) Net Without Stand (Ibs): 6.8 Surface Treatment: Anti-Glare, Hard Coating (3H) Net (Kg): 4.8 COMPATIBILITY Net (Kg): 4.8 PC Resolution (max): 1920x1080 JIMENSIONS (IMPERIAL) (WXHXD) PC Operating System: Wilndows 10/11 certified; macOS tested Physical (in.): 24.22 x 15.78-21.69 x 8.47 Physical Without Stand (in.): 24.22 x 15.78-21.69 x 8.47 Physical Without Stand (in.): 24.22 x 14.33 x 1.89 CONNECTOR Joint HDCP 2.2): 2 Disham Audio Out: 1 HDMI 2.0 (with HDCP 2.2): 2 Physical (im.): 790 x 483 x 147 Power in: D C Socket (Center Positive) Physical without Stand (mm): 615.07 x 400.79-550.79 x 215.05 POWER Consu	Curvature:	Flat	Swivel:	30°
Technology:	Refresh Rate (Hz):	180	Tilt (Forward/Back):	-5° / 25°
Low Blue Light:		Yes (G-Sync compatible)	Pivot (Right/Left):	90° / 90°
Net (lbs): 10.6		, , ,	WEIGHT (IMPERIAL)	
NTSC: 80% size (Typ) sRGB: 113% size (Typ) sRGB: 13.9			Net (lbs):	10.6
Pixel Size:		NTSC: 80% size (Typ) sRGB:	Net Without Stand (lbs):	6.8
Net (kg):			Gross (lbs):	13.9
COMPATIBILITY Net Without Stand (kg): 3.1 PC Resolution (max): 1920x1080 Gross (kg): 6.3 Mac® Resolution (max): 1920x1080 DIMENSIONS (IMPERIAL) (WXHXD) PC Operating System: Windows 10/11 certified; macOS tested Packaging (in.): 31.1 x 19 x 5.8 Physical (in.): 24.22 x 15.78-21.69 x 8.47 Physical (in.): 24.22 x 14.33 x 1.89 CONNECTOR DIMENSIONS (METRIC) (WXHXD) Packaging (mm): 790 x 483 x 147 HDMI 2.0 (with HDCP 2.2): 2 Physical (mm): 615.07 x 400.79-550.79 x 215.05 Power in: DC Socket (Center Positive) Physical Without Stand (mm): 615.07 x 364.1 x 47.96 POWER GENERAL Eco Mode (Conserve): 18W Regulations: CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO Consumption (typical): 29W XG27G1 x1, Displayport Cable (x1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Voltage: AC 100-240V Recycle/Disposal: Please dispose of in accordance with local, state or federal laws. Power Supply: External Power Adaptor Warranty: "Warranty offered may differ fro	Pixel Size:	0.311 mm (H) x 0.311 mm (V)	WEIGHT (METRIC)	
PC Resolution (max): 1920x1080 Gross (kg): 6.3 Mac® Resolution (max): 1920x1080 DIMENSIONS (IMPERIAL) (WXHXD) PC Operating System: Windows 10/11 certified; macOS tested Packaging (in.): 31.1 x 19 x 5.8 Mac® Resolution (min): 1920x1080 Physical (in.): 24.22 x 15.78-21.69 x 8.47 CONNECTOR DIMENSIONS (METRIC) (WXHXD) 3.5 mm Audio Out: 1 HDMI 2.0 (with HDCP 2.2): 2 DisplayPort: 1 Physical (mm): 790 x 483 x 147 Power in: DC Socket (Center Positive) Physical (mm): 615.07 x 400.79~550.79 x 215.05 POWER Eco Mode (Conserve): 18W Regulations: CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO Consumption (typical): 23W Regulations: XG27G1 x1, DisplayPort Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power pluy x1 or 2 (by country) Voltage: AC 100-240V Recycle/Disposal: Please dispose of in accordance with local, state or federal laws. Power Supply: External Power Adaptor ADDITIONAL HARDWARE Marranty: <td>Surface Treatment:</td> <td>Anti-Glare, Hard Coating (3H)</td> <td>Net (kg):</td> <td>4.8</td>	Surface Treatment:	Anti-Glare, Hard Coating (3H)	Net (kg):	4.8
Mac® Resolution (max): PC Operating System: Windows 10/11 certified; macOS tested Windows 10/11 certified; macOS tested Packaging (in.): Physical (in.): 24.22 x 15.78-21.69 x 8.47 Physical (in.): 24.22 x 14.33 x 1.89 DIMENSIONS (METRIC) (WXHXD) Packaging (mm): 790 x 483 x 147 Physical (mm): Physical (mm): Power in: Power in: Power in: DC Socket (Center Positive) POWER Eco Mode (Conserve): 18W Eco Mode (optimized): Consumption (typical): Consumption (max): 31W Voltage: AC 100-240V Stand-by: Power Adaptor ADDITIONAL HARDWARE Kensington Lock Slot: I 1 Packaging (in.): 31.1 x 19 x 5.8 Physical (in.): 24.22 x 14.33 x 1.89 DIMENSIONS (METRIC) (WXHXD) Packaging (in.): 24.22 x 14.33 x 1.89 DIMENSIONS (METRIC) (WXHXD) Packaging (mm): 790 x 483 x 147 Physical (mm): 615.07 x 400.79~550.79 x 215.05 Physical (mm): 615.07 x 364.1 x 47.96 GENERAL CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO XC27G1 x1, DisplayPort Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Stand-by: Power Supply: External Power Adaptor ADDITIONAL HARDWARE Kensington Lock Slot: I 1	COMPATIBILITY		Net Without Stand (kg):	3.1
PC Operating System: Windows 10/11 certified; macOS tested Physical (in.): 24.22 x 15.78~21.69 x 8.47 Physical Without Stand (in.): 24.22 x 14.33 x 1.89 DIMENSIONS (METRIC) (WXHXD) Packaging (mm): 790 x 483 x 147 Physical (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Power in: DC Socket (Center Positive) POWER Eco Mode (Conserve): 18W Eco Mode (optimized): 23W Consumption (typical): 29W Consumption (max): 31W Voltage: AC 100-240V Stand-by: 0.5W Power Adaptor ADDITIONAL HARDWARE Kensington Lock Slot: 1	PC Resolution (max):	1920x1080	Gross (kg):	6.3
PC Operating System: Mac® Resolution (min): 1920x1080 Physical (in.): 24.22 x 15.78~21.69 x 8.47 Physical (in.): 24.22 x 14.33 x 1.89 DIMENSIONS (METRIC) (WXHXD) Packaging (mm): 790 x 483 x 147 Physical (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Ph	Mac® Resolution (max):	1920x1080	DIMENSIONS (IMPERIAL) (WXHXD)	
Mac® Resolution (min): DONNECTOR 3.5mm Audio Out: HDMI 2.0 (with HDCP 2.2): Power in: DC Socket (Center Positive) POWER Eco Mode (Conserve): Eco Mode (optimized): Consumption (typical): Consumption (max): Voltage: AC 100-240V Stand-by: Power Supply: External Power Adaptor Mac® Resolution (min): 1920x1080 Physical (in.): 24.22 x 15.78~21.69 x 8.47 Physical (without Stand (in.): 24.22 x 14.33 x 1.89 DIMENSIONS (METRIC) (WXHXD) Packaging (mm): 790 x 483 x 147 Physical (mm): 615.07 x 400.79~550.79 x 215.05 Physical (mm): 615.07 x 364.1 x 47.96 GENERAL Regulations: CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO VkrSEPRO XG27G1 x1, DisplayPort Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Stand-by: Power Supply: External Power Adaptor ADDITIONAL HARDWARE Kensington Lock Slot: 1	PC Operating System:	,	Packaging (in.):	31.1 x 19 x 5.8
CONNECTOR 3.5mm Audio Out: HDMI 2.0 (with HDCP 2.2): DisplayPort: DC Socket (Center Positive) Physical (mm): Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 364.1 x 47.96 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 400.79~550.79 x 215.05 Physical Without Stand (mm): 615.07 x 40.79~50.79 x 215.05 Physical Without Stand (mm): 615.07 x 40.79~50.79 x 215.05 Physical Without Stand (mm): 615.07 x 40.79~50.79 x 215.05 Physical Without Stand (mm): 615.07 x 40.79 x 615.07 x 40.79 x 615.07			Physical (in.):	24.22 x 15.78~21.69 x 8.47
3.5mm Audio Out: HDMI 2.0 (with HDCP 2.2): DisplayPort: DC Socket (Center Positive) POWER Eco Mode (Conserve): Eco Mode (optimized): Consumption (typical): Consumption (max): Voltage: AC 100-240V Stand-by: Power Supply: ADDITIONAL HARDWARE Kensington Lock Slot: ADDITIONAL HARDWARE Beaution: DMENSIONS (METRIC) (WXHXD) Packaging (mm): 790 x 483 x 147 Physical (mm): 615.07 x 400.79-550.79 x 215.05 Physical (mm): 615.07 x 364.1 x 47.96 GENERAL Regulations: CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO XG27G1 x1, DisplayPort Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Recycle/Disposal: Warranty: *Warranty offered may differ from market to market *Warranty offered may differ from market to market	, ,	1920x1000	Physical Without Stand (in.):	24.22 x 14.33 x 1.89
HDMI 2.0 (with HDCP 2.2): DisplayPort: 1 Power in: DC Socket (Center Positive) POWER Eco Mode (Conserve): Eco Mode (optimized): Consumption (typical): Consumption (max): 31W Voltage: AC 100-240V Stand-by: Power Adapter Adapter ADDITIONAL HARDWARE Fending (mm): 790 x 483 x 147 Fypox 400.79~550.79 x 215.05 Physical (mm): 615.07 x 364.1 x 47.96 GENERAL Regulations: CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO XG27G1 x1, DisplayPort Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Recycle/Disposal: Warranty: Packaging (mm): 790 x 483 x 147 615.07 x 400.79~550.79 x 215.05 Physical (mm): 615.07 x 400.79~550.79 x 215.05 Physical (mm): 615.07 x 400.79~550.79 x 215.05 Physical (mm): 615.07 x 400.79~550.79 x 215.05 Physical (mm): 615.07 x 400.79~550.79 x 215.05 Physical (mm): 615.07 x 400.79~550.79 x 215.05 Physical (mm): 615.07 x 400.79~550.79 x 215.05 Physical (mm): 615.07 x 400.79~550.79 x 215.05 Physical (mm): 615.07 x 400.79~550.79 x 215.05 Physical (mm): 615.07 x 400.79~50.79 x 215.05 Physical (mm): 615.07 x 400.79 x 483 x 147 Physical (mm): 615.07 x 400.79 x 483 Physical (mm): 615.07 x 400.79 x 483 Physical (mm): 615.07 x 400.79 x 483 Physical (mm): 615.07 x 40.79 x 483 Physical (mm): 615.07 x 400.79 x 483 Physical (mm): 615.07 x 400.79 x 483 Physical (mm): 615.07 x 400.79 x 483 Phys			, ,, ,	
DisplayPort: 1			Packaging (mm):	790 x 483 x 147
Power in: Power in: DC Socket (Center Positive) Physical Without Stand (mm): GENERAL Eco Mode (Conserve): Eco Mode (optimized): Consumption (typical): Consumption (max): Voltage: AC 100-240V Stand-by: Power Supply: ADDITIONAL HARDWARE DC Socket (Center Positive) Physical Without Stand (mm): GENERAL Regulations: CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO XG27G1 x1, DisplayPort Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Recycle/Disposal: Warranty: Physical Without Stand (mm): 615.07 x 364.1 x 47.96 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO XG27G1 x1, DisplayPort Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Stand-by: Power Supply: Recycle/Disposal: Warranty: *Warranty offered may differ from market to market Warranty:	,		Physical (mm):	
FOWER Eco Mode (Conserve): 18W Eco Mode (optimized): 23W Consumption (typical): 29W Consumption (max): 31W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: External Power Adaptor ADDITIONAL HARDWARE Kensington Lock Slot: 1 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO AC 23W XG27G1 x1, DisplayPort Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Recycle/Disposal: Please dispose of in accordance with local, state or federal laws. *Warranty offered may differ from market to market			Physical Without Stand (mm):	615.07 x 364.1 x 47.96
Eco Mode (Conserve): Eco Mode (optimized): 23W Consumption (typical): 29W Consumption (max): 31W PACKAGE CONTENTS: Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Stand-by: Power Supply: ADDITIONAL HARDWARE Kensington Lock Slot: 1 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO XG27G1 x1, DisplayPort Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Recycle/Disposal: Warranty: *Warranty offered may differ from market to market		20 contact (contact t contro)	GENERAL	
Regulations: REACH, WEEE, EAC, UkrSEPRO Consumption (typical): 29W Consumption (max): Voltage: AC 100-240V Stand-by: Power Supply: ADDITIONAL HARDWARE Regulations: REACH, WEEE, EAC, UkrSEPRO XG27G1 x1, DisplayPort Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Recycle/Disposal: Warranty: Please dispose of in accordance with local, state or federal laws. Warranty: *Warranty offered may differ from market to market		18W		REACH, WEEE, EAC,
Consumption (typical): Consumption (max): 31W PACKAGE CONTENTS: Adapter x1, DisplayPort Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Stand-by: Power Supply: External Power Adaptor ADDITIONAL HARDWARE Kensington Lock Slot: 1 KG27G1 x1, DisplayPort Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Recycle/Disposal: Warranty: *Warranty offered may differ from market to market	,		Regulations:	
Consumption (max): Voltage: AC 100-240V Stand-by: Power Supply: ADDITIONAL HARDWARE Kensington Lock Slot: AC 100-240V PACKAGE CONTENTS: PACKAGE CONTENTS: (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) Recycle/Disposal: Warranty: Warranty offered may differ from market to market	, ,	29W		(v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by
Voltage: AC 100-240V Stand-by: 0.5W Power Supply: External Power Adaptor ADDITIONAL HARDWARE Kensington Lock Slot: 1 Kensington Lock Slot: 2 Kensington Lock Slot: 3 Kensington Lock Slot: 2 Kensington Lock Slot: 3		31W	PACKAGE CONTENTS:	
Stand-by: 0.5W Power Supply: External Power Adaptor ADDITIONAL HARDWARE Kensington Lock Slot: 1 Recycle/Disposal: Please dispose of in accordance with local, state or federal laws. *Warranty: *Warranty offered may differ from market to market	. ,			
Power Supply: External Power Adaptor ADDITIONAL HARDWARE Kensington Lock Slot: 1 Kecycle/Disposal: with local, state or federal laws. *Warranty: *Warranty offered may differ from market to market to market to market	· ·		Daniela (Diana	• •
ADDITIONAL HARDWARE Warranty: *Warranty offered may differ from market to market Kensington Lock Slot: 1			Recycle/Disposal:	
Kensington Lock Slot: 1			Warranty:	
Cable Organization: Yes		1		market to market
	Cable Organization:	Yes		