PN-HY431

Slim and lightweight digital signage displays



- Make an impact with the 43" display in your retail or corporate environments
- Enhanced and true representation of colour shown from wide colour gamut
- Show and hear content easily with integrated 4K USB media player and speakers
- Slim, sleek and elegant design to suit any setting
- Brightness of 500 candela

- Showcase images and video in detail with 4K Ultra HD resolution (3840 x 2160 pixels)
- Continuous display of content during business operating hours 16/7
- Latest HDMI Connectivity for 4K at 60Hz
- Flexible installation in portrait, landscape, face up, face down and tilted
- 4000:1 contrast ratio



Specifications

DISPLAY MODULE DATA

Panel Technology TFT LCD
Native Resolution (Pixels) 3840 x 2160
Diagonal Size (inches / cm) 43 / 107
Aspect Ratio 16:9

Backlight Technology W-LED / Full Array

 Brightness (cd/m2)
 500

 Contrast Ratio
 1200:1

 Display Colours
 1,06 Billion

 Response Time (grey to grey avg) ms
 8

 Viewing Angle (H/V)0 CR>10
 178 / 178

POWER SUPPLY AND OPERATING ENVIRONMENT

Operating Voltage(ACV) / Frequency(Hz)100-240 / 50-60Power Consumption (W) (Operating MAX)100Power Consumption (W) (Standby)0,50Operating Temperature (oC)0 - 40Humidity (%)20 - 80RH

INSTALLATION

Landscape .
Portrait .
Horizontal .

Mounting (VESA/Number of Points/Pitch mm) VESA / 4 / 200 x 200

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

Audio RCA R-L 1

KEY SPECIFICATIONS

 24/7 Operation Certified
 •

 Built in Speakers (W)
 10W + 10W

 Computer Input - Plug and Play
 •

 Power Management
 •

 Cabinet Colour
 Black

WEIGHTS AND MEASURES

Product Dimensions (W/H/D) mm 973 x 561 x 63,5 Product Weight Without Stand (Kg) 11,5

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI 3 VGA 1 Audio 3.5mm Jack 1

Other HDMI2.0 / HDCP 2.2 / CEC

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	1
USB	1







