

**Aspen 4 Microsoft Teams Rooms Bundle**

ADD FLEXIBILITY TO YOUR MTR NEEDS

MTR devices are very popular in today's meeting room, and with good reason as they are easy to use and offer most features a meeting needs. The only thing they lack is flexibility, which this bundle easily fixes. We updated our i3CONNECT Studio software to present the best meeting room companion available.

-  ENERGY SAVING
- EASY TO USE
- FAST AND PRECISE

FAST AND PRECISE

Where traditional all-in-one MTR screens can suffer from delay when writing, our bundle shines. The Aspen 4 features a precise touch recognition and the intuitive i3CONNECT Whiteboard has been developed in-house for fast operation and user-friendly features.

FULLY INTERACTIVE WITH i3CONNECT STUDIO

One major limitation in MTR devices is that the experience is not truly interactive. Until now.

We updated our i3CONNECT Studio software, so every annotation you make and every piece of whiteboarding you do during your hybrid meeting is shown to all attendees. This ensures everyone is involved, no matter where they are.



TOP NOTCH SECURITY

Plenty of MTR devices run on Android 10, which becomes obsolete in 2027. Our MTR device is powered by Microsoft's own platform MDEP (Microsoft Device Ecosystem Platform). The touchscreen itself even runs on Android 15, guaranteeing years of uninterrupted meetings.





HIGH QUALITY VISUAL EXPERIENCE WITH MASSIVE POWER SAVING

The Aspen 4 is our best touchscreen to date, with insanely detailed visuals. Colours have never been sharper and blacks have never been deeper thanks to the QLED technology. All of this is empowered by local dimming, turning parts of the screen that are not in use off. This saves loads on your energy bill.

FLEXIBILITY IS KEY

This bundle has been put together to be as flexible as possible:



Full control thanks to i3CONNECT Studio

Running on the i3CONNECT Studio interface, you are in full control of which apps are available from the display and the look and feel of the screen



The right fit for every meeting room

This bundle is available in 4 different sizes, ensuring the right fit for any meeting room, no matter the size



No more cable clutter

No need for a table console, so the screen can be positioned freely without cable clutter or obstruction

i3CONNECT ASPEN 4 SPECIFICATIONS

| DISPLAY PROPERTIES | 55" | 65" | 75" | 86" |
|--------------------|-------------------|----------|----------|----------|
| Model | A4 - 55 | A4 - 65 | A4 - 75 | A4 - 86 |
| Series | i3CONNECT ASPEN 4 | | | |
| Product ID | 10010941 | 10010942 | 10010943 | 10010944 |

| DISPLAY SPECIFICATIONS | | | | |
|--------------------------------------|--|------------------|------------------|-----------------|
| Display Technology | QLED IPS/ADS Liquid Crystal Display (LCD) | | | |
| Backlight technology | QLED (Quantum Dot LED) Direct LED with local dimming | | | |
| Dyn. Backlight Multi-zones | 128 | 160 | 220 | 286 |
| DC dimming (for Flicker Free) | Yes | | | |
| Panel size | 54.64" (1.388mm) | 64.53" (1.639mm) | 74.52" (1.893mm) | 85.6" (2.174mm) |
| Display aspect ratio | 16:9 | | | |
| Native resolution | 3840 x 2160 Pixels - 4K Ultra High Definition | | | |
| Brightness | 500 cd/m ² | | | |
| Contrast ratio (typical) | 10.000:1 | | | |
| Contrast ratio (dynamic) | 1.000.000:1 | | | |
| Viewing angle | 178° / 178° | | | |
| Colour depth | 1.07 billion colors (10 bit) | | | |
| Colour gamut | DCI-P3 92% | | | |
| Response time (typical) | < 8 ms | | | |
| Refresh rate | 60 Hz (@ UHD) | | | |
| Surface | 3.2mm Tempered Optical bonded glass, anti-reflection, 9H/7Mohs | | | |
| Supported orientation | Landscape | | | |
| Life time | 50.000 hours (16/7) | | | |
| Eye fatigue | Eye Protection & Blue light filter | | | |

CONNECTIVITY

| | |
|---------------------------------|--|
| Video & audio input | 3x HDMI 2.1 (CEC + 1x ARC) 1x DP 1.2 3x USB-C: - 1x side, DP1.2 + USB 3.2 Gen 1x1 data 100W - 1x side, DP + USB 2.0 data 65W - 1x top for optional accessory 1x VGA + 1x audio (3.5mm) 1x Microphone in (3.5mm) |
| Video & audio output | 1x HDMI 2.1 out 1x USB-C out 1x Headphone out (3.5mm) 1x SPDIF Optical (TOSLINK) |
| Sensors | Ambient Light Sensor & Motion Sensor |
| Integrated OPS slot | Yes |
| USB ports | 2x USB 3.2 Type A 1x USB 2.0 Type A 3 x USB 3.2 Type B for touch |
| Network connectivity | 2x LAN: RJ-45 connector (10/100/1000Mbps) 1x RS232 (DE-9M) Dual Wi-Fi (Wi-Fi 6; 802.11ax & Wi-Fi 5; 802.11ac) - BT 5.2 |
| Multi-functional button | 1x: Side |

OPERATIONAL SPECIFICATIONS

| | |
|--------------------------|--|
| Operating system | Android 15 - Google® EDLA Certified |
| Memory | 8 GB RAM – 128 GB storage |
| CPU | ARM Cortex-A76*4 & A55*4 (8 cores) |
| GPU | ARM Mali G610 MC4 |
| Interactive touch | Technology: V-SENSE infrared touch recognition Connection protocol: HID (Human Interface Device) Touch accuracy: 0.5 mm Touch points: 50 simultaneous multi-touch points Touch response time: 2 ms Touch refresh rate: 500 Hz OS support: Windows 7 and up, Android 5 and up, Full driverless multitouch on Apple Macbooks natively Linux Ubuntu 18.04 and up & ChromeOS |
| Speakers | 2 x 20 Watt, 1x40 Watt subwoofer Dolby® Certified* *Subwoofer included in 65", 75" & 86" |

For the full Aspen 4 specifications, please visit our website at i3-connect.com

XBAR V50 SPECIFICATIONS

| PHYSICAL SPECIFICATIONS | |
|----------------------------------|--|
| Product dimension (LxWxH) | 650.8 × 76.6 × 95.7 mm / 25.6 × 3.01 × 3.77 in |
| Package dimension (LxWxH) | 750 × 136 × 246 mm / 29.5 × 5.4 × 9.7 in |
| Net weight | 2.8 kg / 6.17 lb |
| Gross weight | 6.0 kg / 13.23 lb |
| CONTENT SHARING | |
| Teams (in meeting) | 1080p@30 |
| Local Sharing (Type-C) | 4K@30 |
| Local Sharing (HDMI) | 4K@30 |
| POWER | |
| Power adapter | AC 100-240 V Input and DC 19V/4.5A Output |
| DEVICE MANAGEMENT | |
| Control and Management | Microsoft Device Management Platform (Microsoft Teams Admin Center/Intune/ Pro management portal) MAXHUB Pivot |
| ENVIRONMENTAL CONDITIONS | |
| Operating temperature | 0°C ~ 40°C / 0°F ~ 104°F |
| Storage temperature | -20°C ~ 60°C / -4°F ~ 140°F |
| Operating humidity | 10% ~ 90% RH |
| Storage humidity | 10% ~ 90% RH |
| Altitude | Below 5000 m |

| CAMERA | |
|------------------------------------|--|
| Camera quantity | 2 |
| Pixel | 50MP × 2 |
| Sensor | 1/1.55 inch |
| Aperture | F/2.4 |
| RESOLUTION & FRAME RATE | |
| H.264 / MJPEG | 3840 × 2160, 2560 × 1440, 1920 × 1080, 1280 × 720, 1024 × 576, 960 × 540, 800 × 600, 640 × 360 |
| YUY2 | 1920 × 1080, 1280 × 720, 640 × 360 |
| ZOOM | 6x Digital Zoom |
| Field of view | 130° (D), 125° (H), 50° (V) |
| Privacy shutter | Electric and automatical lens shutter |
| AI Feature | Auto Framing Speaker Tracking Intelligent Focus Smart Gathering Video Fence Audio Fence |

| OPERATING SYSTEM | |
|-------------------------|------------|
| MDEP | Supported |
| OS | Android 13 |

| NETWORK | |
|-----------------------|---------------------------|
| Wi-Fi | Wi-Fi 6, 2x2 MIMO |
| Wi-Fi Protocol | 802.11 a/ b/ g/ n/ ac/ ax |
| Working band | 2.4 GHz + 5 GHz |
| Bluetooth | 5.2 + BLE |
| Network | 1000 Mbps |

AUDIO

SPEAKER

| | |
|------------------------------|-----------------|
| Speaker Quantity | 2 |
| Sound channel | 2.0 |
| Total power (max.) | 15W + 15W |
| Sound pressure (max.) | 83 dB SPL@1W/1M |
| Frequency range | 80 Hz ~ 20 KHz |

MICROPHONE

| | |
|----------------------------|--|
| Microphone Quantity | 12-mic array |
| Pickup range | 8 m |
| Frequency range | 18 Hz ~ 16 KHz |
| Sensitivity | -36 ± 1 dBFS |
| Sampling | 48 KHz |
| Expansion | Supports 2 expansion microphones |
| AI Feature | Noise Reduction Echo Cancellation Anti-Reverberation AGC Algorithm Full-duplex |

INPUT / OUTPUT PORT

| | |
|--------------|-----------------|
| Ports | USB 3.0 Type-B |
| | USB 2.0 Type-A |
| | HDMI Out |
| | HDMI In |
| | Audio out |
| | RJ45 (internet) |
| | RJ45 (M Link) |
| | DC In |

STANDARD ACCESSORIES


| | |
|--------------------|-----------------------------------|
| Accessories | Power Adapter |
| | AC Cable (1.5m / 4.9ft) |
| | HDMI Cable (3m / 9.8ft) |
| | Ethernet Cable (3m / 9.8ft) |
| | Mounted Components (Ada Standard) |

WARRANTY

| | |
|---|--|
| Standard warranty | Aspen 4: 2 years from shipment XBar V50: 2 years from shipment |
| Extended Warranty (Aspen 4 only) | For education entities: 5 years after registration, additional years available for purchase. For corporate entities: 5 years after registration, additional years available for purchase. |

NOTICE

Size and weight vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product. The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.



ARE READY TO RUMBLE WITH THE ASPEN 4 MTR BUNDLE?

LET'S CONNECT

i3CONNECT HQ
Kleine Schaluinweg 7
3290 Diest, BELGIUM.
info@i3-connect.com
www.i3-connect.com

CONTACT US

Ready for the next step? Go ahead: click that big button, fill in the form and we'll get in touch with you for a demo.