

LCD Projectors

PT-VMQ85 Series

Note: Product availability may vary by country or region.

Smooth and Detailed
4K Images from the
Smallest and Lightest
LCD Projector in its Class



White Models

Black Models

Note: As of May 2026, based on internal research, the PT-VMQ85 is the smallest and lightest 4K LCD projector with over 8,000 lm, and the PT-VMQ75 is the smallest and lightest in its class with over 7,300 lm. Displayed resolution 4K (3840 x 2400 pixels) with Quad Pixel Drive [ON].

■ Main Features

01 | Bright, High-Contrast Detail in Any Space

Panasonic's first 4K¹ LCD projector brings clear, high-contrast detail from the smallest and lightest body in its class², making immersive 4K projection more accessible across a wide range of applications. Quad Pixel Drive 2-axis pixel-shifting technology faithfully reproduces high-resolution content, while up to 8,000 lm³ output maintains bright, richly colored visuals in well-lit rooms. Vivid Green Mode enhances color for sports simulation, while dynamic contrast adds natural depth for a more lifelike viewing experience.

02 | Easy to Handle with Flexible Installation

Compact and lightweight, the VMQ85 Series adapts easily to your space, from golf simulation booths to museums, offices, and classrooms. A 1.6x optical zoom, wide lens shift, and an upgraded suite of adjustment tools simplify image alignment, even around ceiling obstructions or when reusing existing mounts. Built-in features like Angle Monitor support quick single-person setup, while 4K DIGITAL LINK⁴, dual HDMI™ inputs, and scheduling function make for smooth integration and day-to-day operation.

03 | Energy-Efficient, Eco-Conscious Design

High brightness is paired with efficient operation to reduce running costs. Image Detection⁵ and Auto Power On⁶ adjust power use to minimize energy waste when idle or between sessions. Laser light source and ECO Filter reduce cost and waste with up to 20,000 hours⁷ of maintenance-free operation. These features, together with Panasonic's use of around 59%⁸ recycled resins and recyclable packaging, help organizations reduce environmental impact and contribute to a cleaner future.

PT-VMQ85 Series			
	PT-VMQ85	PT-VMQ75	PT-VMQ65
Light Output	8,000 lm ³ / 8,000 lm (ANSI) ⁹ / 8,400 lm (Center) ¹⁰	7,300 lm ³ / 7,300 lm (ANSI) ⁹ / 7,600 lm (Center) ¹⁰	6,500 lm ³ / 6,500 lm (ANSI) ⁹ / 6,800 lm (Center) ¹⁰
Resolution	4K (3840 x 2400 pixels) ¹		



¹ Displayed resolution 4K (3840 x 2400 pixels) with Quad Pixel Drive [ON]. ² As of May 2026, based on internal research, the PT-VMQ85 is the smallest and lightest 4K LCD projector with over 8,000 lm, and the PT-VMQ75 is the smallest and lightest in its class with over 7,300 lm. ³ Measured when [PICTURE MODE] is set to [DYNAMIC], [LIGHT POWER] is set to [NORMAL], [DAYLIGHT VIEW] is set to [OFF], and [AUTO POWER SAVE] is set to [OFF]. Measurement, measuring conditions, and notation method comply with ISO/IEC 21118: 2020 international standards. Value is the average of all products when shipped. ⁴ YPbPr 4:2:0 format only for 4K/60p signals input via 4K DIGITAL LINK. ⁵ Settings cannot be made when [PICTURE] menu -> [DAYLIGHT VIEW] is set to [AUTO], [DYNAMIC CONTRAST] is set to anything other than [OFF], [ECO MANAGEMENT] -> [AUTO POWER SAVE] is set to [OFF], [ECO MANAGEMENT] -> [LIGHT POWER] is set to anything other than [NORMAL], a [TEST PATTERN] is displayed, or there is no signal. Image Detection function is supported when the input signal is transmitted via HDMI™ terminal. ⁶ Settings cannot be made when [STANDBY MODE] is set to [ECO/NETWORK] or when [IN STANDBY MODE] is set to [ON] in the [AUDIO SETTINGS] menu. Auto Power On is supported when the input signal is transmitted via HDMI™ terminal. ⁷ At around 20,000 hours, the light output will have decreased to approximately 50% of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2], temperature 30 °C [86 °F], elevation 700 m [2,297 ft] with 0.15 mg/m³ of particulate matter). The estimated time until light output declines to 50% varies depending on the environment. Filter cleaning cycle: 20,000 hours (under dust conditions of 0.08 mg/m³), 10,000 hours (under dust conditions of 0.15 mg/m³). Filter can be washed and reused up to two times. When washing the filter with water, please follow the procedures listed in the operating instructions. ⁸ By total weight of plastic parts in the projector main unit. Excludes projection lenses, printed circuit boards, labels, cables, connectors, electronic components, optical components, ESD components, EMI component adhesives, and coatings. ⁹ Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped. ¹⁰ Average light-output value of all shipped products measured at the center of the screen in NORMAL Mode. ¹¹ Requires the AI-WM50 Series Wireless Module (sold separately). Availability may vary by country or region.

Other Features

- Supports AMX® DD, PJLink™, Extron XTP®, Crestron Connected™ V2, Crestron XiO Cloud™, IPV6¹
- Data Cloning Function via LAN or USB Memory Devices²
- Supports Widescreen 21:9 video content
- Lens Block Detection Function
- Quick On/Quick Off Mode and Direct Power Off
- Audible feedback for projector ON/OFF via remote
- Built-in 10 W speaker and Audio Standby Mode
- Free 360° installation
- Startup Logo Function
- Presentation Support System

Learn More

For more information, please scan the QR code to access the VMQ85 Series product webpage at our global projector website.



¹ Optional AI-WM50 Series Wireless Module is not compatible with IPV6. ² Data-cloning is supported among models in the same series with the same resolution. Excludes passwords, projector ID, and network settings.

Specifications

Model	PT-VMQ85	PT-VMQ75	PT-VMQ65
Projector type	LCD projectors		
LCD panel	Panel size	0.64 inch (16:10 aspect ratio)	
	Pixels	2,304,000 (1920 x 1200) pixels	
Light source	Laser diodes		
Light output ¹	8,000 lm ² / 8,000 lm (ANSI) ³ / 8,400 lm (Center) ⁴	7,300 lm ² / 7,300 lm (ANSI) ³ / 7,600 lm (Center) ⁴	6,500 lm ² / 6,500 lm (ANSI) ³ / 6,800 lm (Center) ⁴
Time until light output declines to 50 % ⁵	20,000 hours (NORMAL/QUIET), 24,000 hours (ECO)		
Resolution	4K (3840 x 2400 pixels) ⁶		
Contrast ratio ⁷	5,000,000:1 (Full On/Full Off) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1].)		
Screen size (diagonal)	0.76–7.62 m (30–300 in), 16:10 aspect ratio		
Center-to-corner zone ratio ²	85 %		
Lens	1.6x manual zoom (throw ratio: 1.09–1.77:1), manual focus lens, F=1.58–1.91, f=15.30–24.60 mm		
Digital Zoom Extender ⁷	Throw ratio 1.09–2.21:1 ⁸ (Corresponding value. When used together with optical zoom.)		
Lens shift (From the origin point of the lens mounter)	Vertical	+44 %	
	Horizontal	±20 %	
Keystone correction range	Vertical ±25°, Horizontal ±35°		
Terminals	HDMI™ 1/2 IN	HDMI™ x 2 (Compatible with HDCP, Deep Color, 4K/60p signal input), CEC supported ⁹	
	HDMI™ OUT	HDMI™ x 1, CEC not supported	
	AUDIO IN	M3 stereo mini-jack x 1	
	AUDIO OUT	M3 stereo mini-jack x 1	
	SERIAL IN	D-sub 9-pin (female) x 1 for computer control (RS-232C compliant)	
	DIGITAL LINK/LAN	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase™ compliant), 100Base-TX (Compatible with PJLink™ [Class 2], HDCP, Deep Color, 4K/60p ¹⁰ signal input)	
	LAN	RJ-45 x 1 for network control, 10Base-T, 100Base-TX, compatible with PJLink™ [Class 2]	
USB (VIEWER/WIRELESS/DC OUT)	USB connector (Type A) x 1 for Memory Viewer function, optional AJ-WM50 Series Wireless Module, power supply (DC 5 V, maximum 2 A ¹¹)		
Protocol versions	IPv4, IPv6 ¹²		
Power supply	Single-phase AC 100–240 V, 50/60 Hz		
Maximum power consumption ¹³	405 W (4.2–1.7 A) (410 VA) (Power consumption is 390 W at 200–240 V)	350 W (3.6–1.5 A) (355 VA) (Power consumption is 335 W at 200–240 V)	325 W (3.4–1.4 A) (330 VA) (Power consumption is 310 W at 200–240 V)
On-mode power consumption (Operating mode) ^{13, 14}	[NORMAL]	370 W (100–120 V), 355 W (200–240 V)	315 W (100–120 V), 300 W (200–240 V)
	[ECO]	260 W (100–120 V), 250 W (200–240 V)	240 W (100–120 V), 230 W (200–240 V)
	[QUIET 1]	305 W (100–120 V), 295 W (200–240 V)	275 W (100–120 V), 265 W (200–240 V)
	[QUIET 2]	255 W (100–120 V), 245 W (200–240 V)	235 W (100–120 V), 225 W (200–240 V)
Filter ¹⁵	Included (Estimated maintenance time: approx. 20,000 hours)		
Operation noise ²	39 dB (NORMAL/ECO), 34 dB (QUIET 1), 29 dB (QUIET 2)	37 dB (NORMAL/ECO), 32 dB (QUIET 1), 27 dB (QUIET 2)	35 dB (NORMAL/ECO), 30 dB (QUIET 1), 25 dB (QUIET 2)
Dimensions (W x H x D)	399 x 115 x 348 mm (15 23/32" x 4 17/32" x 13 11/16") (Excluding protruding parts) 399 x 133 x 348 mm (15 23/32" x 5 1/4" x 13 11/16") (With legs at shortest position)		
Weight ¹⁶	Approx. 7.4 kg (16.3 lbs)	Approx. 7.0 kg (15.4 lbs)	Approx. 6.9 kg (15.2 lbs)
Operating environment	Operating temperature: 0–45 °C (32–113 °F) ^{17, 18} , Operating humidity: 20–80 % (No condensation)		
Applicable software	Multi Monitoring & Control Software, Projector Network Setup Software, Wireless Projector App for iOS/Android™ ¹⁹		

¹ When [PICTURE MODE] is set to [DYNAMIC], [LIGHT POWER] is set to [NORMAL], [DAYLIGHT VIEW] is set to [OFF], and [AUTO POWER SAVE] is set to [OFF]. ² Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118:2020 international standards. Value is average of all products when shipped. ³ Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped. ⁴ Average light-output value of all shipped products measured at the center of screen in NORMAL Mode. ⁵ Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2]). Estimated time until light output declines to 50 % varies depending on environment. ⁶ Displayed resolution (3840 x 2400 pixels) with Quad Pixel Drive [ON]. ⁷ Resolution decreases when using Digital Zoom Extender. Grid Adjustment, 6-Point Screen Correction, VPI Keystone Correction, and curved-screen correction are not available when using this function. The range of corner adjustment is limited. ⁸ When Digital Zoom Extender is set to 80 %. ⁹ Depending on the connected CEC command compatible device, the link control may not operate normally. ¹⁰ YCbCr 4:2:0 format only for 4K/60p signals input via DIGITAL LINK. ¹¹ On standby, power supply is available with Quick Startup set to ON or Power Management set to Ready. ¹² The optional AI-WM50 Series Wireless Module does not support IPv6. ¹³ Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118:2020 international standards. ¹⁴ On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 100 m (2,297 ft). ¹⁵ Filter cleaning cycle varies depending on the environment. The filter can be washed and reused up to two times. Filter cleaning cycle: 20,000 hours (under dust conditions of 0.08 mg/m³), 10,000 hours (under dust conditions of 0.15 mg/m³). ¹⁶ Average value. May differ depending on the actual unit. ¹⁷ Light output is limited at operating temperatures higher than 30 °C (86 °F), and projectors cannot be operated at altitudes higher than 2,700 m (8,858 ft) above sea level. ¹⁸ When the optional AI-WM50 Series Wireless Module is attached, the operating temperature range becomes 0–40 °C (32–104 °F). ¹⁹ When using the Wireless Projector app, display resolution differs depending on your iOS/Android™ device and the display device. The maximum supported display resolution is WXGA (1280 x 800).

Optional Accessories

- **Ceiling Mount Bracket**
ET-PKL100H (for high ceilings) / ET-PKL100S (for low ceilings)
Note: ET-PKL100H/PKL100S used in combination with ET-PKV400B (sold separately).
- **Projector Mount Bracket**
ET-PKV400B
- **Replacement Filter Unit**
ET-RFV500
- **ET-FMP50 Series Media Processors**
ET-FMP50 / ET-FMP20
Note: Product availability may vary by country or region. Visit <https://docs.connect.panasonic.com/projector/products/fmp50> for more information.
- **Wireless Module**
AJ-WM50 Series
Note: Product availability may vary by country or region. The suffix at the end of the model number is omitted. Operating temperature: 0–40 °C (32–104 °F).
- **Wireless Presentation System PressIT**
TY-WPS2 (basic set)
Note: Product availability may vary by country or region. Visit <https://docs.connect.panasonic.com/prodisplays/products/ty-wps/> for more information.

Panasonic



For more information about Panasonic projectors, please visit:
 Projector Global Website – <https://docs.connect.panasonic.com/projector/>
 Facebook – www.facebook.com/panasonicprojectoranddisplay
 YouTube – www.youtube.com/user/PanasonicProjector
 LinkedIn – <https://www.linkedin.com/company/panasonic-projector-and-display/>
 X – https://x.com/Panasonic_PND/

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Availability of products and accessories may vary by country or region. Products may be subject to export control regulations. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade Dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. Trademark PJLink is a trademark applied for trademark rights in Japan, the United States of America and other countries and areas. Android is a trademark or registered trademark of Google LLC. iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license. Windows® is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. "Panasonic" is a registered trademark of Panasonic Holdings Corporation and is used under license from Panasonic Holdings Corporation. MEVIX, SOLID SHINE, and PressIT are trademarks of Panasonic Projector & Display Corporation. All other trademarks are the property of the respective trademark owners. © Panasonic Projector & Display Corporation 2026.

All information included here is valid as of May 2026.

PT-VMQ85_Series_G1 Printed in Japan.