

DTEN D7X 55"

WINDOWS EDITION

Multi-Platform Video Conferencing & Meeting Collaboration Solution

Join Zoom, Microsoft Teams or virtually any other video collaboration meeting with DTEN D7X all-in-one, video, audio, and touch technology for Windows environments.

SPECIFICATIONS



Software	Windows IoT
All-in-One	Multi-Touch 55" Display Native Zoom Rooms, Native Microsoft Teams certification in process 4K Camera 15-Microphone Array 2x Integrated Speakers Wall Mount Included
Bring Your Own Device (BYOD)	Smart Connect via single charging USB-C Cable (included) or HDMI In + USB Extension of display via USB-C(computer must support USB-C Alt-mode DisplayPort) Touchback feature on Windows and Mac OS Use D7X Camera, Microphone, Touch and Speakers with any Software Client HDMI Ingest for monitor and content sharing modes Laptop charging (up to 65W)
Display	LED 55" Ultra HD 4K / 16:9 20 touch-points Low latency- 50 ms response time 180 touch-point reporting rate AI based to improve the touch accuracy Supports dual screens with extended screen support available
Camera System	Field of View (FOV) 129° Vertical FOV 88° PTZ and preset Zoom Rooms Auto framing Zoom Rooms Smart Gallery DTEN Smart Framing
Audio System	15-Microphone Array 2 - integrated Stereo Speakers Acoustic Echo Cancellation Automatic Gain Control (AGC) Automatic Noise Reduction
Inputs & Outputs	PC Module: HDMI out x 1 (CEC, HDCP2.2) USB-A 3.1 x 4 3.5-mm Jack x 1 (Mic + Headphone) Ethernet 1 GigE (RJ45) x 1 On D7X Module: HDMI In x 1 (CEC, HDCP1.4, Dolby AC3) USB-C: USB3.1 Data + DP1.4 + 65W charging

DTEN D7X 55"

WINDOWS EDITION

Multi-Platform Video Conferencing & Meeting Collaboration Solution



SPECIFICATIONS CONT'D

Network	Ethernet (RJ-45) 1 GigE Wi-Fi 802.11a/b/g/n/ax (Support WiFi i6) IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static HTTP/HTTPS Proxy Support Bluetooth 5.2
VESA	400 x 300 mm
Power	100 to 240 V AC, 50 to 60 Hz
Product Dimensions	49 x 30.5 x 2.13 in (1245 x 774 x 54 mm)
Product Weight	47 lbs(21.3 kg)
Packaging Dimensions	53.8 x 34.5 x 6.4 in (1367x877x162 mm) / With an outer box
Packaging Weight	63.7lb. (28.9 kg)
Operating Temperature and Humidity	Operating Temperature 0°C to 40°C Storage Temperature -10°C to 60°C Operating Humidity 20% to 80% RH Storage Humidity 10% to 60% RH
Services Available	DTEN Orbit Service
In the Box	DTEN D7X 55 x1 Wall Mount x1 Stylus x1 Power cord x 5 (Type B,D,F,G,I) USB-C cable x 1 (For BYOD) Antenna x 2 Product Guide

DTEN D7X 75"

WINDOWS EDITION

Multi-Platform Video Conferencing & Meeting Collaboration Solution

Join Zoom, Microsoft Teams or virtually any other video collaboration meeting with DTEN D7X all-in-one, video, audio, and touch technology for Windows environments.

SPECIFICATIONS



Software	Windows IoT
All-in-One	Multi-Touch 75" Display Native Zoom Rooms, Native Microsoft Teams certification in process 4K Camera 15-Microphone Array 2x Integrated Speakers Wall Mount Included
Bring Your Own Device (BYOD)	Smart Connect via single charging USB-C Cable (included) or HDMI In + USB Extension of display via USB-C(computer must support USB-C Alt-mode DisplayPort) Touchback feature on Windows and Mac OS Use D7X Camera, Microphone, Touch and Speakers with any Software Client HDMI Ingest for monitor and content sharing modes Laptop charging (up to 65W)
Display	LED 75" Ultra HD 4K / 16:9 20 touch-points Low latency- 50 ms response time 180 touch-point reporting rate AI based to improve the touch accuracy Supports dual screens with extended screen support available
Camera System	Field of View (FOV) 129° Vertical FOV 88° PTZ and preset Zoom Rooms Auto framing Zoom Rooms Smart Gallery DTEN Smart Framing
Audio System	15-Microphone Array 2 - integrated Stereo Speakers Acoustic Echo Cancellation Automatic Gain Control (AGC) Automatic Noise Reduction
Inputs & Outputs	PC Module: HDMI out x 1 (CEC, HDCP2.2) USB-A 3.1 x 4 3.5-mm Jack x 1 (Mic + Headphone) Ethernet 1 GigE (RJ45) x 1 On D7X Module: HDMI In x 1 (CEC, HDCP1.4, Dolby AC3) USB-C: USB3.1 Data + DP1.4 + 65W charging

DTEN D7X 75"

WINDOWS EDITION

Multi-Platform Video Conferencing & Meeting Collaboration Solution



SPECIFICATIONS CONT'D

Network	Ethernet (RJ-45) 1 GigE Wi-Fi 802.11a/b/g/n/ax (Support WiFi i6) IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static HTTP/HTTPS Proxy Support Bluetooth 5.2
VESA	800 x 400 mm
Power	100 to 240 V AC, 50 to 60 Hz
Product Dimensions	66.1 x 39.5 x 2.18 in (1679 x 1004 x 55.4 mm)
Product Weight	79.6 lbs (36.1 kg)
Packaging Dimensions	73.0 x 44.6 x 7.6 in (1865 x 1135 x 195 mm) / With an outer box
Packaging Weight	112.9 lbs. (51.2 kg)
Operating Temperature and Humidity	Operating Temperature 0°C to 40°C Storage Temperature -10°C to 60°C Operating Humidity 20% to 80% RH Storage Humidity 10% to 60% RH
Services Available	DTEN Orbit Service
In the Box	DTEN D7X 75 x1 Wall Mount x1 Stylus x1 Power cord x 5 (Type B,D,F,G,I) USB-C cable x 1 (For BYOD) Antenna x 2 Product Guide

DTEN D7X 55"

ANDROID EDITION

Multi-Platform Video Conferencing & Meeting Collaboration Solution

Join Zoom, Microsoft Teams or virtually any other video collaboration meeting with DTEN D7X all-in-one, video, audio, and touch technology for Android environments.

SPECIFICATIONS



Software	DTEN OS
All-in-One	Multi-Touch 55" Display Native Zoom Rooms, Native Microsoft Teams certification in process 4K Camera 15-Microphone Array Integrated Speakers Wall Mount Included
Bring Your Own Device (BYOD)	Smart Connect via single charging USB-C Cable (included) or HDMI In + USB Extension of display via USB-C (computer must support USB-C Alt-mode DisplayPort) Touchback feature on Windows and Mac OS Use D7X Camera, Microphone, Touch and Speakers with any Software Client HDMI Ingest for monitor and content sharing modes Laptop charging (up to 65W)
Display	LED 55" Ultra HD 4K / 16:9 20 touch-points Low latency- 50 ms response time 180 touch-point reporting rate AI based to improve the touch accuracy Supports dual screens
Camera System	Field of View (FOV) 129° Vertical FOV 88° DTEN Smart Framing
Audio System	15-Microphone Array Integrated Stereo Speakers Acoustic Echo Cancellation Automatic Gain Control (AGC) Automatic Noise Reduction
Inputs & Outputs	USB-A 3.0 x 2 3.5 mm Audio jack x 2 (headphone and mic) HDMI in x 1 (CEC, HDCP2.2, Dolby AC3) HDMI out x 1 (CEC) USB-C x 2 (USB3.0 Data + DP 1.4 + 65W PD) Ethernet 1 GigE (RJ45) x 1

DTEN D7X 55"

ANDROID EDITION

Multi-Platform Video Conferencing & Meeting Collaboration Solution



SPECIFICATIONS CONT'D

Network	Ethernet (RJ-45) 1 GigE Wi-Fi 802.11a/b/g/n/ax (Support WiFi 6E) IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static HTTP/HTTPS Proxy Support Bluetooth 5.2
VESA	400 x 300 mm
Power	100 to 240 V AC, 50 to 60 Hz
Product Dimensions	49 x 30.5 x 2.13 in (1245 x 774 x 54 mm)
Product Weight	48.3 lbs(21.9 kg)
Packaging Dimensions	53.8 x 34.5 x 6.4 in (1367x877x162 mm) / With an outer box
Packaging Weight	65lbs (29.5 kg)
Operating Temperature and Humidity	Operating Temperature 0°C to 40°C Storage Temperature -10°C to 60°C Operating Humidity 20% to 80% RH Storage Humidity 10% to 60% RH
Services Available	DTEN Orbit Service
In the Box	DTEN D7X 55 x1 Wall Mount x1 Stylus x1 Power cord x 5 (Type B,D,F,G,I) USB-C cable x 1 (For BYOD) Antenna x 2 Product Guide

DTEN D7X 75"

ANDROID EDITION

Multi-Platform Video Conferencing & Meeting Collaboration Solution

Join Zoom, Microsoft Teams or virtually any other video collaboration meeting with DTEN D7X all-in-one, video, audio, and touch technology for Android environments.

SPECIFICATIONS



Software	DTEN OS
All-in-One	Multi-Touch 75" Display Native Zoom Rooms, Native Microsoft Teams certification in process 4K Camera 15-Microphone Array Integrated Speakers Wall Mount Included
Bring Your Own Device (BYOD)	Smart Connect via single charging USB-C Cable (included) or HDMI In + USB Extension of display via USB-C (computer must support USB-C Alt-mode DisplayPort) Touchback feature on Windows and Mac OS Use D7X Camera, Microphone, Touch and Speakers with any Software Client HDMI Ingest for monitor and content sharing modes Laptop charging (up to 65W)
Display	LED 75" Ultra HD 4K / 16:9 20 touch-points Low latency- 50 ms response time 180 touch-point reporting rate AI based to improve the touch accuracy Supports dual screens
Camera System	Field of View (FOV) 129° Vertical FOV 88° DTEN Smart Framing
Audio System	15-Microphone Array Integrated Stereo Speakers Acoustic Echo Cancellation Automatic Gain Control (AGC) Automatic Noise Reduction
Inputs & Outputs	USB-A 3.0 x 2 3.5 mm Audio jack x 2 (headphone and mic) HDMI in x 1 (CEC, HDCP2.2, Dolby AC3) HDMI out x 1 (CEC) USB-C x 2 (USB3.0 Data + DP 1.4 + 65W PD) Ethernet 1 GigE (RJ45) x 1

DTEN D7X 75"

ANDROID EDITION

Multi-Platform Video Conferencing & Meeting Collaboration Solution



SPECIFICATIONS CONT'D

Network	Ethernet (RJ-45) 1 GigE Wi-Fi 802.11a/b/g/n/ax (Support WiFi 6E) IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static HTTP/HTTPS Proxy Support Bluetooth 5.2
VESA	800 x 400 mm
Power	100 to 240 V AC, 50 to 60 Hz
Product Dimensions	66.1 x 39.5 x 2.18 in (1679 x 1004 x 55.4 mm)
Product Weight	80.84 lbs (36.67 kg)
Packaging Dimensions	73.0 x 44.6 x 7.6 in (1865 x 1135 x 195 mm) / With an outer box
Packaging Weight	114.1 lbs. (51.77 kg)
Operating Temperature and Humidity	Operating Temperature 0°C to 40°C Storage Temperature -10°C to 60°C Operating Humidity 20% to 80% RH Storage Humidity 10% to 60% RH
Services Available	DTEN Orbit Service
In the Box	DTEN D7X 75 x1 Wall Mount x1 Stylus x1 Power cord x 5 (Type B,D,F,G,I) USB-C cable x 1 (For BYOD) Antenna x 2 Product Guide