

Key **Features**

- Blur Busters 2.0 Certified
- 240Hz Refresh Rate
- Fast-IPS Display with VESA DisplayHDR 400
- <0.5ms MPRT Response Time
- AMD FreeSync™ Premium



Product **Description**

Engineered for gaming, the ViewSonic XG2431 features the perfect blend of speed, control and color. An ultra-smooth 240Hz display pushes FPS gaming into new territory, enabling games to run at higher frames for superior graphics performance. AMD FreeSync™ Premium synchronizes the monitor and GPU outputs, eliminating screen tearing and lag. Fast-IPS technology combines rich colors with VESA DisplayHDR, better contrast, and wide viewing angles, with up to 4X reponse times compared to traditonal panels. The <0.5ms MPRT response time allows every input to be faster and more precise. Flexible connectivity via DisplayPort and two HDMI ports make connections to other peripherals or high-end graphics cards for gaming a breeze. The XG2431 is also equipped with ViewSonic's exclusive ViewMode™ presets, which offer user-customized game modes, including FPS, RTS and MOBA game settings.

Visit Us

www.viewsonic.com



Parallel Contact Roll 100 1 (19) 100 1			WEIGHT (IMPERIAL)	
Part Type Part Tarthology Part P	Display Size (in.):	24	Net (lbs):	15
March Marc	Viewable Area (in.):	23.8	Net Without Stand (lbs):	7.8
Recolution Symma Contract Nation Contract	Panel Type:	IPS Technology	Gross (lbs):	19
Net Windows Rainer 1,001-1 (typ) 1.5	Resolution:	1920 x 1080	WEIGHT (METRIC)	
December Control Relation Mark 1	Resolution Type:	FHD (Full HD)	Net (kg):	6.8
	Static Contrast Ratio:	1,000:1 (typ)	Net Without Stand (kg):	3.5
Land Support Land Support Supp	Dynamic Contrast Ratio:	80M:1	Gross (kg):	8.6
Proposition	High Dynamic Range:	HDR10	DIMENSIONS (IMPERIAL) (W	VXHXD)
Project Proj	Light Source:	LED	Packaging (in.):	27.5 x 15.7 x 7.3
Delication Space Ricigion Space Ri	Brightness:	350 cd/m² (typ)	Physical (in.):	21.3 x 17.09~20.48 x 9.4
Package Temper	Colors:	16.7M	Physical Without Stand (in.):	21.3 x 12.7 x 1.9
Page	Color Space Support:	8 bit true	DIMENSIONS (METRIC) (WX	HXD)
Page	Aspect Ratio:	16:9	Packaging (mm):	698 x 400 x 185
Manage 176	Response Time (Typical GTG):	1ms	Physical (mm):	540 x 434.1~520.1 x 239
Carectainer First			Physical Without Stand (mm):	540 x 323 x 49
Clarestrice Fact			GENERAL	
Refueblis (Augustin Plate) Versible (Augustin Plate) FreeSymp Premium, G-Symb compatible Premium (G-Symb Compatible) Software solution Refueblish Rade Versible (Augustin Plate)				
Namaba Refeash Rate			Regulations:	WEEE, EAC, UkrSEPRO, RCM, GEMS, VCCI, PSE, K
Television Tel		270		
Picker Prese Pre	Technology:		PACKAGE CONTENTS:	XG2431 x1, 3-pin Plug (IEC C13 / CEE22) x1, Display Cable (v1.2; Male-Male) x1, USB A/B Cable (v3.2; Mal Male) x1, Quick Start Guide x1
Color Gamut: NTSC: 72% size (Typ) sRGB: 104% size (Typ) Warranty: "Warranty offered may differ from market to ma			Recycle/Disposal:	
Place Size				
Surface Treatment: Anti-Glare, Hard Coating (3H) OMPATIBILITY FO Residuline (max): 1920:1080 Mace Resolution (max): 1920:1080 Mace Resolution (mix): 1920:1080 Mace Resolution (mix): 1920:1080 ONNECTOR USB 3.2 Type A Down Stream: 2 USB 3.2 Type B Up Stream: 1 3.5 mm Audio Qut: 1 1.5 mm Audio Qut: 1 2.5 mm Audio Audi			Warranty:	*Warranty offered may differ from market to market
### 1920 1920				
P.C. Resolution (max): 1920x1080 Mace Resolution (max): 1920x1080 P.C. Operating System: Windows 7888 x110/11 eartified: mac/OS tested Mace Resolution (min): 1920x1080 P.C. Operating System: Windows 7888 x110/11 eartified: mac/OS tested Mace Resolution (min): 1920x1080 P.C. Operating System: 1 1.		Anti-Glare, Hard Coating (3H)		
Mace Resolution (max): 1920x1080 PC Operating System: Windows 78/86.1/10/11 certifled; mac/O5 tested Make/2 Resolution (mis): 1920x1080 PONNECTOR USB 3.2 Type B Down Stream: 2 13.5mm Audio Out: 1 2.5mm Audio Out: 1 Prover in: 3-pin Socket (IEC C14 / CEE22) UDIO UTBERS SYSTEM		4020,4000		
PC Operating System: Windows 7/8/8.1/10/11 certified; macOS tested				
Mace® Resolution (min): 1920x1080 ONNECTOR USB 3.2 Type B Up Stream: 2 USB 3.2 Type B Up Stream: 1 1.				
100 100				
USB 3.2 Type B Up Stream: 1 3.5mm Audio Out: 1 HDMI 2.0: 2 DisplayPort: 1 1 Power in: 3-pin Socket (IEC C14 / CEE22) UDIO UD	Mac® Resolution (min): CONNECTOR	1920x1080		
1.5. 1.5.	USB 3.2 Type A Down Stream:	2		
Display Port 1	USB 3.2 Type B Up Stream:	1		
DisplayPort: 1	3.5mm Audio Out:	1		
Power in: 3-pin Socket (IEC C14 / CEE22)	HDMI 2.0:	2		
Multiple	DisplayPort:	1		
Internal Speakers: SWatts x2	Power in:	3-pin Socket (IEC C14 / CEE22)		
### Reco Mode (Conserve): 18W ### Eco Mode (Conserve): 20W ### Consumption (typical): 23W ### Consumption (typical): 23W ### Consumption (max): 52W ### Voltage: AC 100-240V ### Stand-by: 0.5W ### Power Supply: Internal Power Supply ### LODITIONAL HARDWARE ### Rensington Lock Stot: 1 ### Collection Capital Controls: Yes ### CONTROLS ### Physical Controls: Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power) ### Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu ### POPERATING CONDITIONS #### Power Supply: 20% to 90% #### VALL MOUNT ### VALL MOUNT ### VALL MOUNT ### VESA Compatible: 100 x 100 mm ### NPUT SIGNAL ### Frequency Horizontal: ### EDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz ### Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz ### Input Signal ### Power Supplay Power (v1.4): 48 ~ 240Hz ### Input Signal ### Power Supplay Power (v1.4): 48 ~ 240Hz ### Input Signal ### Power Supplay Power (v1.4): 48 ~ 240Hz ### Input Signal ### Power Supplay Power (v1.4): 48 ~ 240Hz ### Input Signal ### Power Supplay Power (v1.4): 48 ~ 240Hz ### Input Signal ### Power Supplay Power (v1.4): 48 ~ 240Hz ### Input Signal ### Power Supplay Power (v1.4): 48 ~ 240Hz ### Input Signal ###	NUDIO			
Eco Mode (Conserve): 16W Eco Mode (optimized): 20W Consumption (typical): 23W Consumption (max): 52W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply Internal Power Supply: Internal Power Supply IDDITIONAL HARDWARE Kensington Lock Slot: 1 Cable Organization: Yes CONTROLS Physical Controls: Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu DEPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% VALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz IDEO INPUT	Internal Speakers:	3Watts x2		
Eco Mode (optimized): 20W Consumption (typical): 23W Consumption (max): 52W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply Ves Consider Organization: Yes Controls: (Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power) Physical Controls: (Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: (Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu PERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Hundidity (non-condensing): 20% to 90% VALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: (HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz	POWER			
Consumption (typical): 23W Consumption (max): 52W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply Internal Power Supply: Internal Power Supply Ves Internal Power Supply: Internal Power Supply Inter	Eco Mode (Conserve):	16W		
Consumption (typical): 23W Consumption (max): 52W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply Internal Power Supply: Internal Power Supply Ves Internal Power Supply: Internal Power Supply Inter	Eco Mode (optimized):	20W		
Consumption (max): 52W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply Internal Power Supply: Internal Power Supply IDDITIONAL HARDWARE Kensington Lock Slot: 1 Cable Organization: Yes CONTROLS Physical Controls: Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu DPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% VALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz VIDEO INPUT				
Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Cable Organization: Yes CONTROLS Physical Controls: Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu PERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% VALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz				
Stand-by: 0.5W Power Supply: Internal Power Supply Internal Power Supply: Internal Power Supply Yes Internal Power Supply: Yes Internal Powe				
Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Cable Organization: Yes CONTROLS Physical Controls: Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu On Screen Display: Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu OPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% VALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz				
ADDITIONAL HARDWARE Kensington Lock Slot: 1 Cable Organization: Yes CONTROLS Physical Controls: Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu OPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% VALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz				
Kensington Lock Slot: Cable Organization: Yes CONTROLS Physical Controls: Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu PERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% VALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz VIDEO INPUT		Internal Power Supply		
Cable Organization: Yes CONTROLS Physical Controls: Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu PERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% VALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz				
CONTROLS Physical Controls: Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu PERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% VALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz VIDEO INPUT				
Physical Controls: Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu PERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% VALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz	Cable Organization:	Yes		
Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu PERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% VALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz	CONTROLS			
### Depth of the composition of the composity of the composition of the composition of the composition of th	Physical Controls:			
Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% VALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz	On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
Humidity (non-condensing): 20% to 90% VALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz				
VALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Horizontal: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz Prequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz	Temperature:			
VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz (IDEO INPUT	Humidity (non-condensing):	20% to 90%		
NPUT SIGNAL Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz	VALL MOUNT			
Frequency Horizontal: HDMI (v2.0): 15 ~ 255KHz, DisplayPort (v1.4): 255 ~ 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz		100 x 100 mm		
Frequency Vertical: 255KHz Frequency Vertical: HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz FIDEO INPUT	NPUT SIGNAL			
IDEO INPUT	Frequency Horizontal:			
	Frequency Vertical: /IDEO INPUT	HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz		



Height Adjust (mm):

Tilt (Forward/Back):

Swivel:

120

90°

-5° / 15°

90° / 0°