

Key **Features**

- Integrated USB-C workstation offers audiovisual and data transfer, and power delivery up to 65W
- USB 3.2 hub with 1 upstream, 2 downstream ports, HDMI, and DisplayPort inputs for easy connectivity
- SuperClear® IPS panel with 100Hz variable refresh rate delivers fluid visuals
- Ergonomic tilt, swivel, pivot and height adjustment capabilities
- TCO, EnergyStar, EPEAT Silver certified for sustainability



Product **Description**

The ViewSonic VG2409-MHDU-2 is a 24" FHD monitor featuring USB 3.2 Hub with 1 upstream, 2 downstream ports, HDMI, and DisplayPort for business and home use. Simplify your work with just one cable that provides audiovisual, data and 65W power transfer. The 100hz variable refresh rate, Eye ProTech technology, and various ViewMode presets cater for optimal screen performance and comfortable viewing without tearing or stuttering. Expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at low energy consumption.



Visit Us

www.viewsonic.com



34 AM \	/iewSonic VG2409-MHDU-2 24" Full HD E	rgonom
DISPLAY		ERG
Display Size (in.):	24	Heig
Viewable Area (in.):	23.8	Swiv
Panel Type:	IPS Technology	Tilt
Resolution:	1920 x 1080	Pivo
Resolution Type:	FHD (Full HD)	WEI
Static Contrast Ratio:	1,300:1 (typ)	Net
Dynamic Contrast Ratio:	50M:1	Net
Light Source:	LED	Gro
Brightness:	350 cd/m² (typ)	WEI
Colors:	16.7M	Net
Color Space Support:	8 bit (6 bit + FRC)	Net
Aspect Ratio:	16:9	Gro
Response Time (Typical GTG):	4ms	DIM
Response Time (GTG w/OD):	4ms	Pac
Viewing Angles:	178º horizontal, 178º vertical	Phy
Backlight Life (Hours):	30000 Hrs (Min)	Phy
Curvature:	Flat	DIM
Refresh Rate (Hz):	100	Pac
Variable Refresh Rate		Phy
Technology:	Yes	Phy
Low Blue Light:	Software solution	GEN
Flicker-Free:	Yes	Reg
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)	
Dival Cina		PAG
Pixel Size:	0.275 mm (H) x 0.275 mm (V)	. 7.
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Box
OMPATIBILITY	4000::4000	Red
PC Resolution (max):	1920x1080	Wa
Mac® Resolution (max):	1920x1080	Pov
PC Operating System:	Windows 10/11 certified; macOS tested	
Mac® Resolution (min):	1920x1080	
ONNECTOR	•	
USB 3.2 Type A Down Stream:	2	
USB 3.2 Type B Up Stream:	1	
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1 (65W power charger)	
3.5mm Audio Out:	1	
HDMI 1.4:	1	
DisplayPort:	1	
Power in:	3-pin Socket (IEC C14 / CEE22)	
UDIO		
Internal Speakers:	2.5Watts x2	
OWER		
Eco Mode (Conserve):	18W	
Eco Mode (optimized):	20W	
Consumption (typical):	22W	
Consumption (max):	24W	
Voltage:	AC 100-240V	
Stand-by:	0.5W	
Stand-by: Power Supply:	Internal Power Supply	
DOWER SUPPLY:	internal Fower Supply	
Kensington Lock Slot:	1	
Cable Organization:	Yes	
CONTROLS	res	
Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)	
Filysical Collilois.		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu	
PPERATING CONDITIONS Temperature:	32°F to 104°F (0°C to 40°C)	
Humidity (non-condensing):	20% to 90%	
VALL MOUNT		
VESA Compatible:	100 x 100 mm	
NPUT SIGNAL		
Frequency Horizontal:	30 ~ 125KHz	
Frequency Vertical:	48 ~ 100Hz	
IDEO INPUT		

ERGONOMICS		
Height Adjust (mm):	130	
Swivel:	360°	
Tilt (Forward/Back):	-3.5° / 28°	
Pivot (Right/Left):	90° / 90°	
WEIGHT (IMPERIAL)		
Net (lbs):	12.3	
Net Without Stand (lbs):	7.7	
Gross (lbs):	15.9	
WEIGHT (METRIC)		
Net (kg):	5.6	
Net Without Stand (kg):	3.5	
Gross (kg):	7.2	
DIMENSIONS (IMPERIAL) (WXHXD)		
Packaging (in.):	24.5 x 20.5 x 5.7	
Physical (in.):	21.25 x 15.35~20.47 x 9.18	
Physical Without Stand (in.): 21.25 x 12.72 x 2	
DIMENSIONS (METRIC) (WXHXD)		
Packaging (mm):	622 x 520 x 144	
Physical (mm):	539.7 x 389.89~519.89 x 233.29	
Physical Without Stand (mm): 539.7 x 323.18 x 50.9	
GENERAL		
Regulations:	Energy Star, EPEAT, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 9.0, EAC, UkrSEPRO	
PACKAGE CONTENTS:	VG2409-MHDU-2 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1	
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.	
Warranty:	*Warranty offered may differ from market to market	
Power Management:	Energy Star standards, EPEAT	



Digital Sync:

TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2), Micro-Packet - Type C