



IISIGNAGEBOX-1

The IISIGNAGEBOX-1 is a compact Android signage box that can be connected to any compatible large format display, enabling immediate use of the iiSignage2 software. With iiSignage2, content can be easily created, scheduled and managed remotely via a secure cloud-based platform, making it a convenient and efficient solution for professional signage environments.



Your display, now signage ready

Turn any compatible display into a powerful digital signage solution by connecting the iiSignagebox-1, with iiSignage² ready to use.



iiSignage²

iiSignage² is our digital signage content management platform to easily show and control your content and to manage your displays in a secure way. The Content Management System (CMS) gives you total control of your messaging and advertising remotely and safely.

01 DEVICE

CPU	Octa-core RK3576 (4x A53 + 4x A72)
RAM	4 GB
WiFi	IEEE802.11ax/ac/a/b/g/n
LAN (RJ45)	x10M100M
USB	3.0 x(DC5V, 500mA) 1, 2.0 x1
HDMI Out	x1 (CEC)
Audio	Mini jack x1

02 TECHNICAL SPECIFICATION

VESA maximum	200 x 75mm

03 POWER MANAGEMENT


Power supply unit	external
Power usage	1.2W typical

04 DIMENSIONS / WEIGHT

Product dimensions W x H x D	216 x 105 x 21.8mm
Weight (without box)	0.66kg
EAN code	4948570033492

05 ENVIRONMENTAL CONDITIONS

Operation temperature range	0°C - 40°C
Operation humidity	10 % - 80%
Storage temperature range	- 20°C - 60°C
Storage humidity	10 % - 90%



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED