

ViewSonic®

LCD DISPLAY

VX3276-MHD-3


Key Features

- SuperClear® IPS Technology
- Frameless Bezel and metallic triangle stand
- Full HD 1080p resolution
- Flicker-Free and Blue Light Filter
- HDMI, DisplayPort and VGA inputs



Product Description

The ViewSonic VX3276-MHD-3 is the perfect blend of style and performance with features that include a sizeable 32" (31.5" viewable) Full HD display and minimalist design. With an ultra-slim profile, metallic silver triangle stand, and sleek edge-to-edge frameless bezel, the monitor has a premium feel that fits nicely both at home and in the office. VX3276-MHD-3 features 1080p resolution, IPS-type panel technology and dual integrated speakers to produce astonishing visual and sound effect from multimedia contents.

**Visit Us**www.viewsonic.com

DISPLAY

Display Size (in.):	32
Viewable Area (in.):	31.5
Panel Type:	IPS Technology
Resolution:	1920 x 1080
Resolution Type:	FHD (Full HD)
Static Contrast Ratio:	1,200:1 (typ)
Dynamic Contrast Ratio:	80M:1
Light Source:	LED
Brightness:	250 cd/m² (typ)
Colors:	16.7M
Color Space Support:	8 bit true
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	75
Variable Refresh Rate Technology:	Yes
Blue Light Filter:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Flicker-Free:	HDR10
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.364 mm (H) x 0.364 mm (V)
Surface Treatment:	Anti-Glare (Semi-Glossy), Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	48~75Hz for HDMI/DP
Mac® Resolution (min):	1920x1080

CONNECTOR

VGA:	1
3.5mm Audio In:	1
3.5mm Audio Out:	1
HDMI 1.4:	1
DisplayPort:	1
Power in:	50/60 Hz

AUDIO

Internal Speakers:	2Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	31W
Eco Mode (optimized):	36W
Consumption (typical):	40W
Consumption (max):	27W
Voltage:	Internal Power Supply AC
Stand-by:	26W
Power Supply:	12

CONTROLS

Physical Controls:	70000
On Screen Display:	Key 1 (game mode), Key 2, Key 3, Key 4, Key 5, Key 6 (power)

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

INPUT SIGNAL

Frequency Horizontal:	24 ~ 86KHz
Frequency Vertical:	50 ~ 75Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.4)
Analog Sync:	Separate - RGB Analog

ERGONOMICS

Swivel:	15°
Tilt (Forward/Back):	Matt° / -4°
Pivot (Right/Left):	0° / 0°

WEIGHT (IMPERIAL)

Net (lbs):	13.7
Net Without Stand (lbs):	12.3
Gross (lbs):	18.1

WEIGHT (METRIC)

Net (kg):	6.2
Net Without Stand (kg):	5.6
Gross (kg):	8.2

DIMENSIONS (IMPERIAL) (WXHxD)

Packaging (in.):	31.7 x 20 x 4.3
Physical (in.):	28.1 x 19.8 x 9.1
Physical Without Stand (in.):	28.1 x 16.4 x 1.5

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm):	806 x 509 x 109
Physical (mm):	713 x 504 x 230
Physical Without Stand (mm):	713 x 416 x 38

GENERAL

Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, BIS
PACKAGE CONTENTS:	VX3276-MHD-3 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market