



HUB5D-L120-3M-UK

Rechargeable powerHub 5 midi tower with three UK AC mains outlets and 1200 Wh battery



Battery capacity
1200 Wh rechargeable LiFePO4
Power outlets
Three UK mains sockets in a powerDome
Mobility
Five-star base with lockable castors
Management
onView cloud service with 3-year subscription

Product overview

The Zioxi HUB5D-L120-3M-UK is a mobile, table-height rechargeable AC power bank designed to provide mains power where fixed wall sockets are unavailable or inconvenient. Its 1200 Wh lithium iron phosphate battery feeds three UK mains outlets housed in a top-mounted powerDome, making it suitable for laptops, displays and other moderate-power equipment in classrooms, meeting spaces and flexible working areas.

- + Truly mobile power: Operates without a mains connection during use and recharges from one standard wall socket.
- + Long-life battery: Replaceable lithium iron phosphate technology rated for approximately 2400 full recharge cycles.
- + Fast recharge: Approximately 2.5 hours from fully discharged for the 1200 Wh battery.
- + Built-in protection: Soft start, low/over-voltage, short-circuit, overload and over-temperature protection.
- + Smart cloud management: onView provides remote control, charge scheduling, battery-health monitoring, alerts and usage information.

Dimensions: 790 H x 350 mm diameter

Technical specifications

Product code	HUB5D-L120-3M-UK
Manufacturer	Zioxi
Product family	powerHub 5 rechargeable midi tower
Product type	Mobile rechargeable AC power bank
Battery capacity	Approximately 1200 Wh
Battery technology	Deep-cycle, rechargeable and replaceable lithium iron phosphate (LiFePO4)
Battery cycle life	Approximately 2400 full recharge cycles
Recharge time	Approximately 2.5 hours from fully discharged
Power outputs	Three UK AC mains outlets in a powerDome
AC output voltage	220-240 V AC
UK outlet protection	Each UK socket fitted with a 3.15 A fuse
Safety protection	Soft start, low/over-voltage, short-circuit, overload and over-temperature protection
Power input	One mains socket required for recharging
External dimensions	790 H x 350 mm diameter
Mobility	Five-star base with lockable wheels
Construction	White powder-coated aluminium housing
Top finish	Compact laminate; white or lime green standard, other colours subject to availability
Cloud management	Zioxi onView web console and mobile app
Included subscription	3-year onView subscription
Wireless requirement	Wi-Fi connection required for onView, warranty support and battery-health management
Warranty	2 years for the powerHub and electronics; battery covered by battery manufacturer's warranty
Regional configuration	UK outlets and UK recharge lead; EU and other regional options available

Usage limitation: The AC outlets are intended for moderate-power equipment. Do not use the powerHub with high-load appliances such as kettles, heaters or vacuum cleaners.

onView functions

- Remote power control and scheduled charging.
- Green-charge scheduling based on lower-carbon grid periods.
- Battery-health, temperature and recharge alerts.
- Usage, location and historical reporting.

Specification source: Zioxi rechargeable powerHub 5 product information, checked 3 August 2026. Specifications may be updated by the manufacturer without notice.