

newline



SERIES

65"

75"

86"

ALL-IN-ONE SOLUTION FOR COLLABORATION

Designed for corporate workspace, Newline Z Series brings you immersive and effective meetings. With a camera, 8-microphone array and speakers, all integrated into an interactive display, experience meetings and interact without limitations.



Enhanced
Wi-Fi 6



100W Posered
USB Type-C



Unique 3mm
Narrow Bezel



High Quality
Sound Incl.
Subwoofer



Secure User
Profiles



SDM-S Ready

Z SERIES SPECIFICATION

Product Information	Model Name	TT-6522Z	TT-7522Z	TT-8622Z
Display Specifications	Active Screen Size	65"	75"	86"
	Display Technology	LED		
	Resolution	3840 × 2160 (4K)		
	Display Area	1428 × 803 mm	1650 × 928 mm	1895 × 1066 mm
	Display Ratio	16:9		
	Display Color Depth	1.07 Billion		
	Brightness	400 cd/m ²		
	Contrast Ratio (Dynamic)	5000:1		
	Response Time	8ms		
	Viewing Angle	178°		
	Display Life Time (MTBF)	≥ 50,000 hours		
Power	Working Voltage	AC 100 - 240V Max 6.0A	AC 100 - 240 V Max 6.5A	AC 100 - 240V Max 7.8A
	Standard Power Consumption	190W	200W	210W
	Eco Power Consumption	150W	240W	270W
Transportation/ Storage	Storage Temperature / Humidity	-20°C - 60°C / 20% - 90% RH (Non-Condensing)		
	Working Temperature / Humidity	0°C - 40°C / 20% - 80% RH (Non-Condensing)		
	Mounting (Optional)	Wall-Mounted / Mobile Stand		
	Outline Dimensions (without wall mount bracke thickness)	1497 × 920 × 84 mm	1719 × 1044 × 85 mm	1965 × 1184 × 85 mm
	Packing Dimensions	1640 × 1036 × 207 mm	1859 × 1160 × 227 mm	2119 × 1290 × 250 mm
	Net Weight	36 kg	50 kg	60 kg
	Gross Weight	46.5 kg	64 kg	76 kg

Touch	Touch Sensor	Projective Capacitive (PCAP)
	Touch Surface Technology	Anti-Glare + Anti-Fingerprint + Antimicrobial Tempered Glass
	Transparency	88% ± 3
	Surface Hardness (Mohs)	7H
	Touch Points	20 Points / Optional Windows 40 Points
	Touch Screen Writing Tools	Passive Pen / Fingers
Connectivity	USB Data Ports	1 × USB 3.0 Type-C (PD 65W / Optional 100W) 1 × USB Type-C (No PD) 4 × USB Type-B (Touch) 3 × USB 3.0 Type-A 1 × USB 3.0 Type-A to Android
	Digital Audio-Video Inputs	3 × HDMI In 2.0 1 × DisplayPort 1.2 1 × Microphone In
	Digital Audio-Video Outputs	1 × HDMI Out 2.0 1 × Audio Line Out 1 × S/PDIF
	Integrated PC Slot	1 × OPS-PC Slot 1 × SDM-S Slot
	Control Input	1 × RS-232
	Network	1 × In & 1 × Out RJ-45 Connector
	Proximity Sensor	1
	Wi-Fi Module Slot	1

Embedded Operating System	Chipset	Amlogic 311D2
	RAM	8 GB
	ROM	64 GB
	OS Version	Android 11
	Multimedia File Formats Support	Image: JPEG, BMP, PNG Video: MPEG1, MPEG2, MPEG4, Sorenson H.263, H.263, H.264, MVC, AVS, AVS+, WMV3, VC1, Motion JPEG, VP8, VP9, RV30/RV40 Audio: MPEG1/2 @LAYER1/@LAYER2/@LAYER3, EAC3, ACC-LC, HE-AAC, VORBIS, LPCM, IMA-ADPCM, MS-ADPCM, G711 A/MU-LAW, LBR(COOK), FLAC
Speaker	Position	Top-Front
	Rated Impedance	6Ω
	Frequency Response	180Hz - 20KHz when SPL is -10dB
	Output S.P.L.	0dB ~ -10dB
Microphone	Max Power Output	20W × 2 + 15W Subwoofer × 1
	Position	Upper Front
	Quantity	8-Mic Array
Camera Module	Pickup Distance	8m
	Camera Resolution	4K@30Hz / UHD
	Field of View	120° FOV Lenses
	Resolution	8M
Camera Module	Resolution	8M
	Camera Tile Range	15°

2022 Newline Interactive Inc. Product specifications may vary by region, please contact our local offices for details. Actual product features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.

HEADQUARTERS (TX,USA)

TEL: +1 888 233 0868
info@newline-interactive.com

EUROPE OFFICE

TEL: +34 911169178
info_eu@newline-interactive.com

ASIA PACIFIC OFFICE

TEL: +886 3 550 4768
info_ap@newline-interactive.com

INDIA OFFICE

TEL: 1 800 419 0309
info.in@newline-interactive.com

KOREA OFFICE

TEL: +82 2 2638 5140
koreainfo@newline-interactive.com

newline